

MULTIPURPOSE ELECTRICAL DROP BOLTS

Minilock & Microlock

Export Product-list

January 2024



Ordering information



Q.ty

MODELS

N°

TECHNICAL CHARACTERISTICS	HEAVY DUTY LOCKING BOLT	UNIVERSAL OPERATING VOLTAGE	CURRENT DRAW	BOLT STATUS SENSOR	REGOPLUS® DOOR STATUS SENSOR	F = Frontal flange for flush mounting FZ = Long flange for flush mounting L = Bracket for surface mounting	R = Reversible D = Right hand (DIN links) S = Left hand (DIN recthis)	SERIE BLUELOCK® (fail-secure) security version = bolt 'out' without power SERIE REDLOCK® (fail-safe) anti-panic version = bolt 'out' with power	Export Product-list	Q.ty
Models for recessed mounting. Each solenoi bolt comes with its own counterflange. For surface mounting are available the pertinent BLINDOBOX housing (see page 23).	solid AISI 316 stainless steel Microlock (steel or AISI 303 s. s.)	Vdc	mA	● 1 SPDT dry contact 1A ○ 1 SPDT dry contact 0,5A ● Timed opening (1±20 sec) ● Control of bolt exit ● Interlink (for interlock)	● REGOPLUS® DOOR STATUS SENSOR				Ordering information	
									MODELS	N°
MINILOCK Type F Type L Type FZ	ROUND BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	---	F	R	MINI-BLUELOCK	0081B2RFU 0081B2RLU 0081B2RFZU	
		12/24V	900/450	●	---	L	R	MINI-BLUELOCK		
		12/24V	900/450	●	---	FZ	R	MINI-BLUELOCK		
		12/24V	900/450	●	---	F	R	MINI-REDLOCK		
		12/24V	900/450	●	---	L	R	MINI-REDLOCK		
		12/24V	900/450	●	---	FZ	R	MINI-REDLOCK		
	SLANTED BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	---	F	R	MINI-BLUELOCK	0082B2RFU 0082B2RLU 0082B2(D/S?)FZU	
		12/24V	900/450	●	---	L	R	MINI-BLUELOCK		
		12/24V	900/450	●	---	FZ	D/S ?	MINI-BLUELOCK		
		12/24V	900/450	●	---	F	R	MINI-REDLOCK		
		12/24V	900/450	●	---	L	R	MINI-REDLOCK		
		12/24V	900/450	●	---	FZ	D/S ?	MINI-REDLOCK		
MICROLOCK Type F Type L	ROUND BOLT Ø 8mm stroke 8mm	12V	390	---	---	F/L ?	R	MICRO-BLUELOCK	00801A2R(F/L?) 00801A4R(F/L?) 00801B2R(F/L?) 00801B4R(F/L?) 00803A2R(F/L?) 00803A4R(F/L?) 00803B2R(F/L?) 00803B4R(F/L?)	
		24V	200	---	---	F/L ?	R	MICRO-BLUELOCK		
		12V	390	○	---	F/L ?	R	MICRO-BLUELOCK		
		24V	200	○	---	F/L ?	R	MICRO-BLUELOCK		
		12V	390	---	---	F/L ?	R	MICRO-REDLOCK		
		24V	200	---	---	F/L ?	R	MICRO-REDLOCK		
		12V	390	○	---	F/L ?	R	MICRO-REDLOCK		
		24V	200	○	---	F/L ?	R	MICRO-REDLOCK		
		12V	390	○	---	F/L ?	R	MICRO-REDLOCK		
		24V	200	○	---	F/L ?	R	MICRO-REDLOCK		
Note: See also SLIM-MICROLOCK on page 24										
ADDITIONAL ANCILLARIES FOR MICROLOCK										
TWO-SLIDES COUNTER-STRIKES FOR MICROLOCK a b	Additional accessory for Microlock electrical drop bolts a - two-slides counter-plate for Microlock "F" version for flush mounting a1 - two-slides counter-plate as above but FZ version (20x60mm) including magnet for door status sensor b - two-slides strike block for Microlock "L" version for surface mounting (the strike block is aluminium anodized "silver colour" type).								0080502R 0080502RZ S00809V1RF	
"TRONIX" VERSION with smart micromodule										
MINILOCK with Regopus® Version "FZ"	ROUND BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	●	FZ	R	MINI-BLUELOCK	0081B2RFZUT 0083B2RFZUT	
		12/24V	900/450	●	●	FZ	R	MINI-REDLOCK		
	SLANTED BOLT Ø 15mm stroke 14mm	12/24V	900/450	●	●	FZ	D/S ?	MINI-BLUELOCK		
		12/24V	900/450	●	●	FZ	D/S ?	MINI-REDLOCK		

Note: prices quoted do **not include** key cylinders, handles and other installation accessories. The standard locking counter plate is always supplied with Minilock electrical drop bolts, but for Microlock electrical drop bolt. The electrical drop bolt Minilock and Microlock should be required equipped with additional rod (fitted axially in the rearbody) to provide mechanical release, with extraprize of euro 16,00 each unit.